



### Ducting Angle LUW A

Group: 1621

#### Application

Mounting Angle for rectangular ducts installed directly under the ceiling, or for suspended installation when using a threaded rod.

Types A-SL and A-SZ allow for soundproof installation also according to DIN 4109.

#### Scope of delivery

Types A-SL and A-SZ are equipped with pre-assembled sound absorption head.

#### Installation

Fixing to the duct with rivets (Ø 4 - 5 mm), sheet metal screws (Ø 4 - 5 mm) or M8 bolts.

#### Technical Data

Working load: 0.5 kN for A-L and A-Z  
0.3 kN for A-SL and A-SZ

Material (metal component): Steel, pre-galvanised  
Types A-SL and A-SZ: Up to 8.7 dB(A)

Inserted insulation:

Sound absorption unit: EPDM, black

Temperature range: -50°C up to +100°C

Type	Connection to building structure	Material [mm]	Length of legs [mm]	W [kg]	Quantity [pack]	Part number
A-L	M8/M10	35 x 2	35/85	0.05	100	<b>110496</b>
A-Z	M8/M10	35 x 2	35/46/38	0.05	100	<b>110498</b>
A-SL	M8/M10	35 x 2	35/85	0.06	100	<b>110497</b>
A-SZ	M8/M10	35 x 2	35/46/38	0.06	100	<b>110499</b>