



## Torx Flat Head Coach Screw FLAH

Group: 1369

### Application

Flange screw with perfectly aligned properties for the constructional timber work, available in diameters 8 and 10 mm.

- ◆ Simple handling is secured due to ideal load transmission.
- ◆ The head dia. of type M8 is aligned to the slots of Channel 41. Thus for direct assembly through the elongated hole of the channel, a good load bearing capacity is secured.
- ◆ Type M10 can also be used at the edge of the channel for direct assembly into the elongated holes.
- ◆ The cutting notch allows direct screwing in without pre-drilling and allows a pinpoint locating.
- ◆ In addition, the tip avoids reliably the splitting of the battens behind.
- ◆ The high bearing of loads given by the flat head reduces the necessary fixing points. Especially for the fixing of roof hooks, an economical handling is assured.

### Technical Data

Material: Steel, galvanised

Type	Ø [mm]	Length [mm]	Screw tool	W [kg]	Quantity [pack]	Part number
8/40	8	40	T 40	0.01	50	<b>110804</b>
8/60	8	60	T 40	0.02	50	<b>110805</b>
8/80	8	80	T 40	0.02	50	<b>110806</b>
10/70	10	70	T 40	0.03	50	<b>110807</b>
10/100	10	100	T 40	0.04	50	<b>110809</b>