



### Slide Set GS 2G-PL HCP

Group: 1836

#### Application

Slide Set for single and double mounting of mechanical equipment, to be used on Sikla Channels, brick or concrete walls and on bearers. To be used preferably in combination with Sikla Pipe Clamps Ratio S and Stabil D-3G. Various connection options with these pipe clamps ranging between M10 and R1". For adapters for these connection options (see Adapter AD f/f). Sound absorption by means glass fibre reinforced PA slide rails.

#### Technical Data

Permissible load for ceiling mounting: 0.6 kN  
 Permissible load for floor mounting: 1.2 kN  
 Lever arm  $L_{max}$ : 150 mm  
 Max. Slide path: 140 mm  
 Temperature range (permanent exposure): 130°C

Static friction coefficient  $\mu_0$ : 0.18  
 Sliding friction coefficient  $\mu$ : 0.14

Material: Steel, HCP  
 Metal components: Steel, HCP  
 Slide bar: Polyamide, glass fibre reinforced

Adm. load FZ \* under stress of fire

FWD 30 [N]	FWD 60 [N]	FWD 90 [N]	FWD 120 [N]
≤ 600	≤ 430	≤ 280	≤ 200

FZ = max. adm. load

\* The load capacity of the connecting elements used is to be respected, this applies in particular under stress of fire.

Type	W [kg]	Quantity [pack]	Part number
2G2-PL	0.65	25	<b>114594</b>