




Adapter AD f/f

Group: 1333

Application

Additional connection options for all Sikla Pipe Clamps equipped with 3G triple thread nut, fixed points and threaded tubes.


During assembly the Rod Coupling has to be locked with two hexagon nuts (not included in scope of delivery).

Technical Data

Material:

Form A: Steel, electro-galvanised

Form B: Malleable cast iron, electro-galvanised



Type	Form	Length [mm]	A/F [mm]	W [kg]	Quantity [pack]	Part number
M16/M10	A	35	19	0.05	50	106740
M16/M12	A	35	19	0.04	50	124665
M16/M16	A	30	19	0.03	50	106290
1/2"/M10	A	35	24	0.07	10	146371
1/2"/M12	A	35	24	0.06	25	156639
1/2"/M16	A	40	24	0.07	25	124656
1/2"/1/2"	A	35	24	0.11	10	146380
3/4"/M10	A	35	32	0.15	10	105651
3/4"/M12	A	35	32	0.16	10	105749
3/4"/M16	A	35	32	0.14	10	105660
3/4"/1/2"	A	35	32	0.12	10	146399
1"/M10	B	40	22	0.13	10	105679
1"/M12	B	40	22	0.13	10	105758
1"/M16	B	40	22	0.12	10	105688
1"/1/2"	B	40	27	0.12	10	146405

