



## Ratio S M8

Group: 1234

### Application

One-piece pipe clamp with thread connection M8 for pipes for M&E services. For soundproof wall, floor and ceiling installation (as per DIN 4109).

With time-saving quick-set clip.

### Installation

After pressing together both parts of the clamp, the clamping bolt head must be located behind the angled profiles; then tighten clamping bolt (2 Nm).

### Technical Data

Max. perm. working load (tension)\* 0.37 kN

Material:

Clamp:

Steel (20 mm x 1.0 mm), electro-galvanised

Sound absorption lining:

SBR/EPDM, black (see chapter "Sound Absorption Products").

Sound absorption up to 17 dB(A)

\* The recommended load is calculated using specific statistical methods relating to break load and is designed to restrict deflection to 1.5 mm or 2 % of the maximum applicable clamping diameter.

### Approvals / Conformity



This product has been awarded the RAL quality mark "pipe supports" and is subject to continuous external monitoring according to RAL GZ-655.

Size range [mm]	NB	W [kg]	Quantity [pack]	Part number
10 - 12	10/12 mm	0.03	100	166669
13 - 16	15 mm	0.03	100	157339
17 - 19	3/8"	0.03	100	157366
20 - 24	1/2"	0.04	100	157348
25 - 30	3/4"	0.04	100	157357
31 - 38	1"	0.05	100	157320
40 - 46	1 1/4"	0.05	50	157311
48 - 51	1 1/2"	0.06	50	157302
58 - 63	2"	0.06	50	191864