



**Rubber Profile SAL SBR/EPDM**

Group: 1294

**Application**

Sound absorption lining for steel straps and pipe clamps (also according to DIN 4109). Application up to +110°C.

**Technical Data**

- Material:

SBR/EPDM, black
- Hardness:

45+/-5° Shore
- Temperature range:

-40°C up to +110°C
- Breaking elongation:

min. 500 %
- Tear strength:

400 N/cm<sup>2</sup>
- Fire resistance:

Material category B2 (DIN 4102), non-dripping
- Sound absorption:

Up to18 dB(A)
- Fully resistant to:

Diluted acids, lyes, alkaline solutions, water, aqueous solutions up to 70°C;  
No absorption of moisture
- Partially resistant to:

Grease, mineral oil, animal or vegetable fats, ester and ketones
- Not resistant to:

Hot oils, fuels, aliphatic and aromatic hydrocarbons and chloric gas
- Durability:

Weatherproof, ageing and ozone-resistant, DIN 53508 and 53509 tested

Type	Steel strap [mm]	H [mm]	Number of ribs	Weight [kg/m]	Quantity roll [m]	Part number
STD 1	25 x 3.0	4.5	4	0.19	30	146502
STD 2	30 x 3.0	4.0	4	0.20	30	146511
STD 3	40 x 4.0	6.0	5	0.31	30	146520
STD 4	50 x 5.0	7.0	5	0.39	30	146539
STD 5	70 x 6.0	7.0	7	0.52	30	146548