



Hexagon Bolt SKT

Group: 1370

Technical Data

Thread	Working load (tension)
M8	15.6 kN
M10	24.7 kN
M12	35.9 kN
M16	66.7 kN

Satisfies DIN 933

Material: Steel class 8.8, electro-galvanised

Type	Length [mm]	W [kg]	Quantity [pack]	Part number
M8/20	20	0.01	100	138459
M8/25	25	0.01	100	138431
M8/30	30	0.02	100	138574
M8/40	40	0.02	100	138440
M8/60	60	0.02	100	114705
M8/80	80	0.03	100	114714
M8/100	100	0.04	100	138608
M8/110	110	0.04	100	124975
M10/20	20	0.02	100	138617
M10/25	25	0.02	100	138468
M10/30	30	0.03	100	138626
M10/40	40	0.03	100	114158
M10/60	60	0.04	100	138635
M10/80	80	0.05	50	114723
M10/100	100	0.06	50	114732
M10/120	120	0.07	50	138644
M12/25	25	0.04	100	138662
M12/30	30	0.04	100	138477
M12/40	40	0.05	50	138671
M12/60	60	0.06	50	138680
M12/80	80	0.07	50	138705
M12/100	100	0.09	50	138714
M12/120	120	0.10	50	114750
M16/25	25	0.07	50	138723
M16/30	30	0.08	50	138732
M16/45	45	0.10	50	138741
M16/60	60	0.12	50	138556
M16/80	80	0.14	25	138750
M16/100	100	0.17	25	138769
M16/120	120	0.19	25	114778