



## U Bolt RUB 3570 A HCP

Group: 1810

### Application

For pipeline systems in industrial and residential buildings and Sprinkler installations according to VdS and FM standards.

For horizontal and vertical pipelines, the U-Bolts are applied as Fixed Points and as Guiding Supports.

### Scope of delivery

Four hexagon nuts included in loose form.

### Installation

When used as Guided Support, nuts have to be arranged and fixed on both sides, at the top and at the bottom of the profile. Thereby the pipe should remain flexible. When used as Fixed Point the admissible loads of the connecting elements shouldn't exceed the bending loads of the U-bolt.

### Technical Data

Material: Steel, HCP

Type	NB	B [mm]	L <sub>1</sub> [mm]	L <sub>2</sub> [mm]	Thread	W [kg]	Quantity [pack]	Part number
26.9	3/4"	40	60	40	M 10	0.12	50	162179
33.7	1"	48	66	40	M 10	0.12	50	162188
42.4	1 1/4"	56	76	50	M 10	0.14	50	162197
48.3	1 1/2"	62	82	50	M 10	0.14	50	162203
60.3	2"	76	97	50	M 12	0.23	50	162212
76.1	2 1/2"	94	113	50	M 12	0.26	50	162221
88.9	3"	106	126	50	M 12	0.29	50	162230
114.3	4"	136	155	60	M 16	0.63	25	162249
139.7	5"	164	175	60	M 16	0.71	25	162258
168.3	6"	192	201	60	M 16	0.80	10	162267
193.7		218	233	60	M 16	0.90	10	162276
219.1	8"	248	263	70	M 20	1.61	10	162285
273.0	10"	302	314	70	M 20	1.88	10	162294
323.9	12"	352	365	70	M 20	2.52	1	162300
355.6	14"	402	411	70	M 24	3.53	1	162319
406.4	16"	452	463	70	M 24	3.90	1	162328
508.0	18"	554	565	70	M 24	4.63	1	162337

