

Pipe Loop RSL N ss

Group: 1718

Application

For pipeline installations of fixed fire extinguishing systems, mainly used for Sprinkler systems.

Scope of delivery

Pipe Loop with rounded edges. Flange nuts and cup nuts are included in loose form.


Technical Data

Type	Nominal load [kN]
26.9 - 60.3	2.0
76.1 - 114.3	3.5
133 - 168.3	5.0
219.1	8.5

Material: Stainless steel, A4

Approvals / Conformity

VdS-Approval G4850025; FM-Approval



Type	NB	Connection	D [mm]	H [mm]	W [kg]	Quantity [pack]	Part number
26.9	3/4"	M10	27	65	0.06	100	116621
33.7	1"	M10	34	65	0.06	100	116622
42.4	1 1/4"	M10	43	65	0.06	50	116623
48.3	1 1/2"	M10	49	70	0.06	50	116624
60.3	2"	M10	61	79	0.06	50	116625
76.1	2 1/2"	M10	77	98	0.14	25	116626
88.9	3"	M10	90	113	0.16	25	116627
108		M10	110	142	0.18	25	116628
114.3	4"	M10	115	142	0.20	25	116629
133		M12	135	155	0.22	25	116630
139.7	5"	M12	142	155	0.24	25	116631
159		M12	161	185	0.26	25	116632
168.3	6"	M12	170	185	0.26	25	116633
219.1	8"	M16	221	239	0.56	10	116634